

# FTXL-JV + RXL-M3

Guaranteed heating operation  
down to -25°C



Efficiency data		FTXL + RXL	25JV + 25M3	35JV + 35M3	
Cooling capacity	Min./Nom./Max.	kW	1.2/2.5/3.4	1.3/3.5/3.8	
Heating capacity	Min./Nom./Max.	kW	1.1/3.2/5.5/1.49 (1)	1.2/3.8/6.0/1.99 (1)	
Power input	Cooling	Min./Nom./Max.	kW	0.29/0.80/1.30	
	Heating	Min./Nom./Max.	kW	0.24/0.72/2.14	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+		
		Pdesign	kW	2.50	3.50
		SEER		6.01	5.87
		Annual energy consumption	kWh	146	209
	Heating (Average climate)	Energy label	A+		
		Pdesign	kW	2.50	3.00
		SCOP		4.37	4.21
		Annual energy consumption	kWh	793	998

  

Indoor unit		FTXL	25JV	35JV
Casing	Colour	White		
Dimensions	Unit	HeightxWidthxDepth	mm	
			283x770x198	
Weight	Unit		kg	
			8	
Air filter	Type	Removable / washable / mildew proof		
Sound power level	Cooling	dBA	57	
	Heating	dBA	57	
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dBA	
			41/34/27/23	
	Heating	High/Nom./Low/Silent operation	dBA	
			41/35/29/26	

  

Outdoor unit		RXL	25M3	35M3
Dimensions	Unit	HeightxWidthxDepth	mm	
			550x858x330	
Weight	Unit		kg	
			40	
Sound power level	Cooling	dBA	61	
	Heating	dBA	61	
Sound pressure level	Cooling	High/Low	dBA	
			48/44	
	Heating	High/Low	dBA	
			49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB
				-10~46
	Heating	Ambient	Min.~Max.	°CWB
				-25~18
Refrigerant	Type/Charge/GWP	kg	R-410A/1/1,975	

(Note) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (1) Maximum heating capacity at -15°C outdoor temperature